



LG15.TPLMODLIGHT



Product shown: LG15.TPLMODLIGHT STD showing light on

Designed and manufactured for harsh and rugged environments, providing extra low voltage but high output lighting.

FEATURES

- Part Series: LG15.TPLMODLIGHT
- Classification: Class III Lighting chain
- Maximum string length: 25m
- Supply Cables: 2.5mm² leads length 5m each
- MODLIGHT connection IEC 60309 & Gland
- Built and tested to AS/NZS 60598.2.20 Luminaires - Lighting Chains
- Rough Service rated
- Tough - injection moulded construction, built for Industrial, Marine and Construction applications
- White LED output
- Unit Colour: Black

BENEFITS

- Single Fixture
- Scalable
- Robust for military level use
- High level light output
- Serviceable via an authorised service agent
- Compact and light weight design (1.1kg per fitting)
- Test & Tag not required (extra low voltage)
- Can be manufactured to end-users specifications

SPECIFICATIONS

Voltage	24V DC
Wattage	36W LED per luminaire
Max. string wattage	240W (6 x TPLMODLIGHT)
IP Rating (connected/capped)	IP66/IP67
Max. Ambient Temperature	40°C
Required power supply	Jackson LIFEGUARD® ACS-LV/ELV 24V DC power supply
Dimensions	115(h) x 127(w) x 395(l) mm

