

PRODUCT SPECIFICATION SHEET







CABLE RAMP



Product shown: 2 channel cable ramp. One, four & five channel lengths also available.

BENEFITS

- Much stronger than rubber
- Hinged lid clips shut securely
- Durable and heavy load capacity
- Flame retardant properties
- Electrical insulation properties
- Protects cables and personnel

FEATURES

- Cable Ramps provide an essential protective housing for cables used in indoor and outdoor environments
- Constructed from top quality all weather polyurethane with locking hinged lid and anti skid design
- Provide a safe crossing for vehicles and pedestrian traffic while protecting valuable electrical cables and hose lines
- Ideal for use in all environments including events, industrial environments, oil and gas applications and mining
- Suitable for use with heavy trucks and forklifts up to 20t weight loading per axle
- Two channels to accommodate two cables up to 30mm in diameter
- Interlocking units with corner options available

SPECIFICATIONS	
LOAD WEIGHT	20 tonne per axle
RAMP DIMENSIONS	900(L) x 250(W) x 45(H)mm
RAMP WEIGHT	5kg
CHANNEL DIMENSIONS X2	30(W) x 30(H)mm
MATERIAL	Polyurethane
PRODUCT CODE	CABLE RAMP CR-2

For more information



jackson.co.nz sales@jackson.co.nz 0800 543 348

